

# View transactions

## 3DS2 Transactions

**3DS2 Transactions tab** can be accessed from the left menu and has 4 sections:

- [Search Transactions](#)
- [Transaction List](#)
- [Transaction Details](#)
- [Transaction Messages](#)

Search transactions

From

Transaction date from

To

Transaction date to

3DS Server Transaction ID

3DS Server Transaction ID

Account number

Account number

Min purchase amount

Min purchase amount

Max purchase amount

Max purchase amount

Merchant name

Merchant name

Provider(s)

Provider(s)

Transaction type

Status

Purchase currency

Purchase currency

Message category

Device channel

Message version

3DS Requestor Trans ID

3DS Requestor Trans ID

Clear

Search

Transaction list

Select a row to view details.

Display

10

Records

Showing 1 to 10 of 294,967 Transactions.

Previous

1

2

3

4

5

...

29497

Next

| Provider | Date (dd/mm/yyyy)   | 3DS Server Transaction ID            | Account number   | Amount | Currency | Merchant name | Status               |
|----------|---------------------|--------------------------------------|------------------|--------|----------|---------------|----------------------|
| Visa     | 10/09/2021 04:59:18 | f8fe35ea-140b-4e0e-8b19-f8fc3b05cb85 | 423561XXXXXX0203 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |
| Visa     | 10/09/2021 04:59:18 | 5c623ab8-f8e4-4a1c-bc85-f10645bb2e71 | 423561XXXXXX0195 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |
| Visa     | 10/09/2021 04:59:18 | 720f4804-df4d-4ccb-8c86-b1a36d1389e4 | 423561XXXXXX0187 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |
| Visa     | 10/09/2021 04:59:17 | 071c98ce-5d9e-4de2-bb3c-3aa7aa9303a8 | 423561XXXXXX0153 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |
| Visa     | 10/09/2021 04:59:17 | c2d8aaba-8ef6-4b3d-b534-915080445c41 | 423561XXXXXX0161 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |
| Visa     | 10/09/2021 04:59:17 | c160a717-839d-4c76-adea-1abf8e222bd8 | 423561XXXXXX0179 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |
| Visa     | 10/09/2021 04:59:15 | 17ab77ff-a601-4046-bfde-bfa9bd40c15b | 423561XXXXXX0146 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |
| Visa     | 10/09/2021 04:59:15 | caf57fd2-0d31-4a7d-bcb2-249b258175cc | 423561XXXXXX0138 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |
| Visa     | 10/09/2021 04:59:14 | 1fb5ddd7-0d7b-4abc-bf03-02420428b43  | 423561XXXXXX0120 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |
| Visa     | 10/09/2021 04:59:14 | 30c64dbd-5b27-47af-b238-248f6fba7a43 | 423561XXXXXX0112 | 200.00 | 036      | Test Merchant | Y (ARes: C, RReq: Y) |

## Search transactions

This section allows you to search through the database for specific transactions. You can filter through transactions by entering information about the transaction. Fields include:

- **From** - only include transactions on and after the specified date
- **To** - only include transactions on and before the specified date

- **3DS Server Transaction ID** - only include transactions with the specified Transaction ID
- **Account number** - only include transactions by cardholder account number (may be represented by PAN or token)
- **Minimum purchase amount** - only include transactions above the specified amount
- **Maximum purchase amount** - only include transactions below the specified amount
- **Merchant name** - only include transactions processed by the specified merchant, name must be an exact match
- **Provider(s)** - only include transactions processed by the specified card scheme or schemes
- **Transaction type** - only include transactions of a certain transaction type, by default all are included:
  - **Production:** This option will show all transactions made using the production Directory Server profiles setup on the admin UI only
  - **TestLabs:** If subscribed to the GPayments TestLabs, this option will show transactions made using the TestLabs Directory Server profile only
- **Status** - only include transactions with the specified result status (e.g. "Y" for **Transaction Successful** , etc.)
- **Purchase currency** - only include transactions performed in the specified currency, defined by currency code
- **Message category** - only include transactions that are either PA (Payment) or NPA (Non-Payment)
- **Device channel** - only include transactions performed on a specific platform (e.g. browser, device, 3RI)
- **Message version** - only include transactions with a specific EMV message version
- **3DS Requestor Trans ID** - only include transaction with a specific 3DS Requestor Transaction Id

Once you have set the desired filters, click **Search** to view results in the **Transaction List** below. Click **Clear** to reset the fields.

## Transaction list

Transaction list displays all transactions or a filtered list if you have selected any of the search parameters above.

Transaction details displayed are:

- **Provider** - card scheme used for transaction
- **Date** - date and time that the transaction was processed
- **3DS Server Transaction ID** - 3DS Server transaction ID of the particular transaction
- **Account number** - full account number used in the transaction, may be represented by PAN or token

#### Important

For transactions made using **Auth API v1**, a full PAN is stored encrypted in the database. For **Auth API v2** transactions, PANs are stored in a truncated format (only first 6 and last 4 digits are stored, remaining digits are masked). Therefore, depending on the API version used, some results may be only partially matched based on the **account number** search value. It is recommended to use the other search parameters to narrow down search results if required.

- **Amount** - purchase amount of the transaction
- **Currency** - currency code that the transaction was processed in
- **Merchant name** - name of the merchant processing the transaction
- **Status** - authentication result returned for the transaction, using the formats:
  - **Frictionless (i.e. no challenge)** - "*Final status (ARes: ARes status)*", e.g. "Y (ARes: Y)"
  - **Challenge** - "*Final status (ARes: ARes status)*", RReq: *RReq status*", e.g. "N (ARes: C, RReq: N)"

Select any transaction row to view its details in the Transaction details section below.

## Transaction Details

Transaction details displays the details for the transaction selected in the Transaction list.

Transaction details

|                                                                                                        |                                      |                                       |                                      |                                                                                     |
|--------------------------------------------------------------------------------------------------------|--------------------------------------|---------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------|
| 3DS Server Transaction ID                                                                              | bb1414a4-da5e-44c8-b82d-828e00a1e564 | Purchase date (dd/mm/yyyy)            | 06/02/2020 15:57:41                  |  |
| Merchant ID                                                                                            | 123456789012345                      | Merchant name                         | Test Merchant                        |                                                                                     |
| Account number                                                                                         | 410000XXXXX5000                      | Amount                                | 200.00                               |                                                                                     |
| ThreeDS Requestor name                                                                                 | 3dsclient.local.visa                 | ThreeDS Requestor ID                  | 123456789.visa                       |                                                                                     |
| ARes status                                                                                            | C                                    | RReq status                           | Y                                    |                                                                                     |
| Status reason                                                                                          |                                      | Acquirer BIN                          | 40001                                |                                                                                     |
| Device channel                                                                                         | BRW (Browser-based Authentication)   | Pay token indicator                   |                                      |                                                                                     |
| Authentication value  | AAEBBWGCUwJgAAAAABIJTAAAAA==         | Authentication type                   | Static                               |                                                                                     |
| ECI                                                                                                    | 05                                   | Merchant category code                | 3200                                 |                                                                                     |
| Message category                                                                                       | PA (Payment)                         | Card expiry date                      |                                      |                                                                                     |
| Recurring frequency                                                                                    |                                      | Purchase currency                     | 036                                  |                                                                                     |
| Recurring expiry date                                                                                  |                                      | Challenge mandated                    | N                                    |                                                                                     |
| SDK transaction ID                                                                                     |                                      | DS transaction ID                     | 4cbce215-d3c6-437f-b1d7-cd48ade61cd7 |                                                                                     |
| ACS transaction ID                                                                                     | b7b4a86b-91f2-4aa4-8862-b2f889749f42 | ThreeDS Requestor challenge indicator |                                      |                                                                                     |
| Error code                                                                                             |                                      | Error detail                          |                                      |                                                                                     |
| Error component                                                                                        |                                      | Error description                     | <div></div>                          |                                                                                     |
| Message version                                                                                        | 2.1.0                                |                                       |                                      |                                                                                     |

Requests / Responses

The Transaction details displayed are:

- **3DS Server Transaction ID** - universally unique transaction identifier assigned by the 3DS Server to identify a single transaction
- **Purchase date** - date and time of the purchase
- **Merchant ID** - acquirer assigned merchant identifier. This should be the same value that is used in authorisation requests sent on behalf of the 3DS Requestor
- **Merchant name** - merchant name assigned by the acquirer or payment system
- **Account number** - account number used in the authorisation request for payment transactions, may be represented by PAN or token. The first 6 and last 4 digits of the account number are shown, the remaining digits are masked with a **X** character
- **Amount** - purchase amount of the transaction
- **ThreeDS Requestor name** - DS assigned 3DS Requestor name. Each DS will provide a unique name to each 3DS Requestor on an individual basis
- **ThreeDS Requestor ID** - DS assigned 3DS Requestor identifier. Each DS will provide a unique ID to each 3DS Requestor on an individual basis

- **ARes/RReq status** - indicates whether a transaction qualifies as an authenticated transaction or account verification or not. Possible values are:
  - **Authenticated (Y)** - authentication verification successful
  - **Not Authenticated (N)** - not authenticated/account not verified; transaction denied
  - **Unauthenticated (U)** - authentication/account verification could not be performed; technical or other problem
  - **Attempted (A)** - attempts processing performed; Not authenticated/verified, but a proof of attempted authentication/verification is provided
  - **Challenge Required (C)** - additional authentication is required using the CReq/CRes
  - **Decoupled Authentication (D)** - Challenge Required; Decoupled Authentication confirmed as authentication method
  - **Rejected (R)** - authentication/account verification rejected; Issuer is rejecting transaction/verification and requests that authorisation not be attempted
  - **Informational Only (I)** - 3DS Requestor challenge preference of Information Only acknowledged
- **Status reason** - Provides information on why the Transaction Status field has the specified value. For Payment channel, required if the Transaction Status field = N, U, or R. For Non-payment channel, it is Conditional as defined by the DS. Possible values are:
  - **01** - Card authentication failed
  - **02** - Unknown Device
  - **03** - Unsupported Device
  - **04** - Exceeds authentication frequency limit
  - **05** - Expired card
  - **06** - Invalid card number
  - **07** - Invalid transaction
  - **08** - No Card record
  - **09** - Security failure
  - **10** - Stolen card
  - **11** - Suspected fraud
  - **12** - Transaction not permitted to cardholder
  - **13** - Cardholder not enrolled in service

- **14** - Transaction timed out at the ACS
- **15** - Low confidence
- **16** - Medium confidence
- **17** - High confidence
- **18** - Very High confidence
- **19** - Exceeds ACS maximum challenges
- **20** - Non-Payment transaction not supported
- **21** - 3RI transaction not supported
- **22** - ACS technical issue
- **23** - Decoupled Authentication required by ACS but not requested by 3DS Requestor
- **24** - 3DS Requestor Decoupled Max Expiry Time exceeded
- **25** - Decoupled Authentication was provided insufficient time to authenticate cardholder. ACS will not make attempt
- **26** - Authentication attempted but not performed by the cardholder
- **27–79** - Reserved for EMVCo future use (values invalid until defined by EMVCo)
- **80–99** - Reserved for DS use
- **Acquirer BIN** - Acquiring institution identification code for the merchant's bank
- **Device channel** - Indicates the channel from which the transaction originated. Possible values are:
  - App-based (01-APP)
  - Browser-based (02-BRW)
  - 3DS Requestor Initiated (03-3RI)
- **Pay token indicator** - value of **True** indicates that the transaction was de-tokenised prior to being received by the ACS. This data element will be populated by the system residing in the 3-D Secure domain where the de-tokenisation occurs (i.e. the 3DS Server or the DS). The Boolean value of true is the only valid response for this field when it is present
- **Authentication value** - payment system-specific value provided as part of the ACS authentication for each supported DS. Authentication Value may be used to provide proof of authentication, e.g. during authorisation or clearing. This value is only able to be retrieved via API for 7 days, after which it is truncated. It is always masked on the UI for security reasons.

- **Authentication type** - indicates the type of authentication method the Issuer will use to challenge the cardholder if challenge is required, whether in the ARes message or what was used by the ACS when in the RReq message. Possible values are:
  - **01** - Static
  - **02** - Dynamic
  - **03** - OOB
  - **04** - Decoupled
  - **05–79** - Reserved for EMVCo future use (values invalid until defined by EMVCo)
  - **80–99** - Reserved for DS use
- **ECI** - electronic commerce indicator value for the transaction, which identifies status of cardholder authentication for card schemes
- **Merchant category code** - DS specific code describing the Merchant's type of business, product or service
- **Message category** - identifies the category of the transaction. Possible values are:
  - **01** - PA (Payment)
  - **02** - NPA (Non-Payment)
  - **03–79** - Reserved for EMVCo future use (values invalid until defined by EMVCo)
  - **80–99** - Reserved for DS use
- **Card expiry date** - expiry date of the PAN or token supplied to the 3DS Requestor by the cardholder in **YYMM** format
- **Recurring frequency** - for a recurring transaction, indicates the minimum number of days between authorisations
- **Purchase currency** - currency code in which purchase amount is expressed
- **Recurring expiry date** - for a recurring transaction, date after which no further authorisations shall be performed, in **YYYYMMDD** format
- **Challenge mandated** - indication of whether a challenge is required for the transaction to be authorised due to local/regional mandates or other variable, possible values are:
  - **Y** - Challenge is mandated
  - **N** - Challenge is not mandated
- **SDK transaction ID** - universally unique transaction identifier assigned by the 3DS SDK to identify a single transaction

- **DS transaction ID** - universally unique transaction identifier assigned by the DS to identify a single transaction
- **ACS transaction ID** - universally unique transaction identifier assigned by the ACS to identify a single transaction
- **ThreeDS requestor challenge indicator** - indicates whether a challenge is requested by the merchant for this transaction. For example:
  - For 01-PA, a 3DS Requestor may have concerns about the transaction, and request a challenge.
  - For 02-NPA, a challenge may be necessary when adding a new card to a wallet.
  - For local/regional mandates or other variables.
  - Possible values are:
    - **01** - No preference
    - **02** - No challenge requested
    - **03** - Challenge requested: 3DS Requestor Preference
    - **04** - Challenge requested: Mandate
    - **05** - No challenge requested (transactional risk analysis is already performed)
    - **06** - No challenge requested (Data share only)
    - **07** - No challenge requested (strong consumer authentication is already performed)
    - **08** - No challenge requested (utilise whitelist exemption if no challenge required)
    - **09** - Challenge requested (whitelist prompt requested if challenge required)
    - **10-79** - Reserved for EMVCo future use (values invalid until defined by EMVCo)
    - **80-99** - Reserved for DS use
    - **Note:** If the element is not provided, the expected action is that the ACS would interpret as 01 = No preference.
- **Error code** - if available, code indicating the type of problem identified in the message
- **Error detail** - if available, additional detail regarding the problem identified in the message
- **Error component** - if available, code indicating the 3-D Secure component that identified the error. Possible values are:
  - **C** - 3DS SDK
  - **S** - 3DS Server

- **D - DS**
- **A - ACS**
- **Error description** - if available, text describing the problem identified in the message
- **Message version** - protocol version identifier utilised by the 3DS Server, set in the AReq message. The message version Number does not change during a 3DS transaction

## Transaction Messages

To view the 3DS2 messages for a transaction, click **Requests** / **Responses** at the bottom of the Transactions section.

Message type    AReq

Time stamp    06/02/2020 15:57:43

Message content

```
{
  "notificationURL": "https://testlab.3dsecure.cloud/api/v1/brw/challenge/notification",
  "messageCategory": "01",
  "purchaseDate": "20200206045741",
  "threeDSRequestorRefNumber": "3DS_LOA_SER_GPPL_020100_00075",
  "merchantCountryCode": "840",
  "browserColorDepth": "24",
  "browserJavaEnabled": false,
  "mcc": "3200",
  "purchaseCurrency": "036",
  "browserAcceptHeader": "text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,image/apng,*/*;q=0.8",
  "browserTZ": "0",
  "merchantName": "Test Merchant",
  "threeDSRequestorAuthenticationInd": "01",
  "threeDSRequestorURL": "http://gpayments.com",
  "acctNumber": "410000XXXXX5000",
  "browserScreenHeight": "768",
  "messageType": "AReq",
  "threeDSRequestorName": "3dsclient.local.visa",
  "acquirerMerchantID": "123456789012345",
  "messageVersion": "2.1.0",
  "browserLanguage": "en-US",
  "threeDSRequestorID": "123456789.visa",
  "acquirerBIN": "40001",
  "deviceChannel": "02",
  "browserIP": "XXXXXXXXXXXX",
  "browserUserAgent": "Mozilla/5.0 (Windows NT 6.1; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/73.0.3683.75 Safari/537.36",
  "purchaseAmount": "20000",
  "purchaseExponent": "2",
  "threeDSRequestorOperatorID": "AS_TEST_LAB_OPER_00001",
  "threeDSCompInd": "U",
  "threeDSRequestorURL": "https://testlab.3dsecure.cloud:14443/api/v1/ds/result/request",
  "browserScreenWidth": "1024",
  "threeDSRequestorTransID": "bb1414a4-da5e-44c8-b82d-828e00a1e564"
}
```

- **Message type** - 3DS message type, e.g. AReq, ARes, RReq, RRes, Error
- **Time stamp** - date and time the message was sent or received.
- **Message content** - raw JSON message content that was sent or received.

## 3DS1 Transactions

### Important

A transaction tab will only be added when the current tenant enables 3DS1 capability.

3DS 2
3DS 1

Search transactions

From

Transaction date from

To

Transaction date to

3DS Requestor Transaction ID

3DS Requestor Transaction ID

Account number

Account number

Min purchase amount

Min purchase amount

Max purchase amount

Max purchase amount

Merchant name

Merchant name

Merchant ID

Merchant ID

Purchase currency

Purchase currency

Provider

Clear
Search

Transaction list
Select a row to view details.

Display
10
Records
Showing 1 to 10 of 1,633 Transactions.
Previous
1
2
3
4
5
...
164
Next

**3DS1 Transactions tab** can be accessed from the left menu and has 3 sections.

## Search Transactions

This section allows you to search through the database for specific transactions. You can filter through transactions by entering information about the transaction. Fields include:

- **From** - only include transactions on and after the specified date
- **To** - only include transactions on and before the specified date
- **3DS Requestor Trans ID** - only include transaction with a specific 3DS Requestor Transaction Id
- **Account number** - only include transactions by cardholder account number
- **Minimum purchase** amount - only include transactions above the specified amount
- **Maximum purchase** amount - only include transactions below the specified amount
- **Merchant name** - only include transactions processed by the specified merchant, name must be an exact match
- **Merchant ID** - only include transactions processed by the specified merchant, Id must be an exact match
- **Purchase currency** - only include transactions performed in the specified currency, defined by currency code
- **Provider(s)** - only include transactions processed by the specified card scheme

## Transaction List

Transaction list displays all transactions or a filtered list if you have selected any of the search parameters above.

Transaction details displayed are:

- **Provider** - card scheme used for transaction
- **Date** - date and time that the transaction was processed
- **3DS Requestor Transaction ID** - 3DS Requestor transaction ID of the particular transaction
- **Account number** - full account number used in the transaction, may be represented by PAN or token
- **Amount** - purchase amount of the transaction
- **Currency** - currency code that the transaction was processed in
- **Merchant name** - name of the merchant processing the transaction
- **Acquirer Merchant ID** - the Id of the merchant set by the acquirer

## Transaction Details

Transaction details displays the details for the transaction selected in the Transaction list.

| Transaction details          |                                      |                       |                  |
|------------------------------|--------------------------------------|-----------------------|------------------|
| 3DS Requestor Transaction ID | 42d3feef-faf7-49f7-8482-223bd8203b31 | Trans Status          | Y                |
| Transaction date             | 2021-11-17T02:47:51                  | Merchant ID           | 123456789012345  |
| Merchant name                | Test Merchant                        | Account number        | 410000XXXXXX0100 |
| Amount                       | 100.00                               | Recurring frequency   |                  |
| Purchase currency            | 036                                  | Recurring expiry date |                  |



The Transaction details displayed are:

- **ThreeDS Requestor ID** - DS assigned 3DS Requestor identifier. Each DS will provide a unique ID to each 3DS Requestor on an individual basis
- **Trans Status** - only include transactions with the specified result status (e.g. "Y" for Transaction Successful, etc.)
- **Date** - date and time that the transaction was processed
- **Merchant name** - name of the merchant processing the transaction

- **Account number** - account number used in the authorisation request for payment transactions, may be represented by PAN or token. The first 6 and last 4 digits of the account number are shown, the remaining digits are masked with a X character
- **Amount** - purchase amount of the transaction
- **Recurring frequency** - for a recurring transaction, indicates the minimum number of days between authorisations
- **Purchase currency** - currency code in which purchase amount is expressed
- **Recurring expiry date** - for a recurring transaction, date after which no further authorisations shall be performed, in YYYYMMDD format