Manage nodes


ActiveServer can be run in either a **single node** or **multi node** setup. The details for these nodes can be viewed on the **Deployment** page under the **Nodes** tab. This is also where you can set the logging level for a particular node, if it requires a different setting to the system wide log level setting.

Info

A guide on multi node setups will be provided in a future document version.

User Access

A user requires the **System admin** role to view and edit node settings.



Copyright ©2019 GPayments Pty Ltd. All rights reserved.

Node details

Select a node from the **Node list** to view its details:

- **Node name** - editable name that can be given to the node to keep track of status.
- **Node ID** - system generated UUID for the node in the database.
- **Operating system** - operating system being used for the node's server.
- **Java version** - Java version being used for the node's server.
- **Physical memory size** - total amount of physical memory installed on the node's server.
- **CPU architecture** - type of CPU architecture chip installed on the node's server.
- **Cores** - amount of logical cores installed on the node's server.
- **IP address** - IP address that the node is hosted on.

Logging

If a different level of logging is required for a particular node, the following settings can be changed:

- **Use system default** - If ***Enabled***, the node will use the system wide log level setting. If ***Disabled***, log level for the node can be changed manually.
- **Log level** Available to be edited if **Use system default** is ***Disabled***, allowing the log level to be changed.

Copyright ©2019 GPayments Pty Ltd. All rights reserved.